

1. BASIC CARE AND MAINTENANCE

The beauty of Ezer Masonry™ is that it is virtually maintenance free. To clean dust or other debris that has settled on the surface of the veneer use a dry whisk broom and lightly brush. You can also use a soft bristle brush and a mix of mild detergent and water to clean the surface. Be sure to rinse surface thoroughly afterwards.

2. EFFLORESCENCE

Ezer Masonry™ uses quality ingredients in mix designs that substantially improves performance of our Masonry Veneer. Mortars used to install our veneer — or concrete products adjacent to our veneer — may develop a white film called efflorescence that may drip or run onto the face of the veneer. Efflorescence is a white, chalky film caused by moisture migrating through other concrete products. When it evaporates, a salt deposit is left on the surface. It will disappear over time if the moisture source is controlled or eliminated. A simple solution of 5 parts vinegar to 1 part water will remove efflorescence.

3. SEALING

Should you chose to apply a sealer to the surface of the veneer as a protectant against the elements, select a penetrating Silane or Siloxane water-based sealer recommended for manufactured stone and masonry veneer. The sealer should be tested on a small, inconspicuous section before overall application. The Sealer Manufacturer's recommendations must be followed.

Visit: ezermasonry.com/resources for complete installation instructions.